

# BioHawk LF<sup>®</sup>

## Automated Detection, Collection, and Bioidentification

The BioHawk LF<sup>®</sup> is an automated system for detecting, collecting and identifying airborne pathogens based on bio-fluorescent detection and multi-analyte lateral flow immunoassay (ticket) identification. The system will sample a targeted air stream for a period of up to months without human intervention. Upon detection of a suspicious aerosol, the bioidentification process can be programmed to occur automatically or may alternatively be manually initiated.



*BioHawk LF<sup>®</sup> system for automated detection, collection, and bioidentification*

Results are provided through an onboard display and serial digital data link.

The biodetector-triggered assay mode significantly lowers operating costs. Assays are only performed when a bioaerosol has been detected, and there is no lag between processing and testing. This is in contrast to protocols where assays are run at fixed intervals or in batch product processing where each batch must be tested before release.

Using commercial, off-the-shelf bioassay tickets, the presence of up to eight biothreat agents may be determined in a time period of 5 to 15 minutes. Bioassay tickets are provided in hermetically-sealed carrier modules that are loaded into the instrument. Loaded carrier modules are viable for several months and provide the ultimate in automated long-term bio-surveillance.

Machine vision methods are used to determine the presence of pathogens. There is no need to educate users on assay interpretation. Assays are insensitive to ambient light level or color balance. A transfer vial is standard for after-assay storage of sample fluid for use with an alternative confirmation method.

Bioassay ticket testing is perhaps the most widely used and mature technology for the identification of biothreats at trace levels. Tickets have a long shelf life, typically 12 to 18 months, and require no special storage conditions. Bioassay tickets are available for a variety of possible threats from multiple sources, and tests for new threats are commonly developed as the need arises. The BioHawk LF is obsolescence-resistant in that regard.

## FEATURES

- A sophisticated aerosol biodetector/sampler/wet bioidentifier
- Suitable for toxins, bacteria, spores, fungi, multi-cellular pathogens
- Performs up to 8 simultaneous bioassays on collected samples
- 325 liter/minute air sampling rate
- Hours-long air sampling times
- Uses widely available lateral flow immunoassay tickets
- Room temperature storage of consumables
- Machine vision-based assay protocol
- Incorporates multiple novel patented technologies
- Fast assays: 5 - 15 minutes typ.
- Auto-flush protocol for decontamination and cleaning
- Flash memory retains data for over 6,000 assays

## APPLICATION AREAS

- Mailrooms
- Air quality
- Agriculture
- Public Health
- Medical facilities
- Homeland security
- Military
- Power plants

The biodetector and automated ticket assay module are patented technologies that are also used in other Research International products – notably the Ancam 6100 and VBAD 3600 – systems that are currently in use by world governments to determine the presence of airborne pathogens.

The BioHawk LF is particularly well-suited for use as part of a complete CBRN monitoring program. It is cost-competitive, reliable and user friendly; its high degree of sampling and bioassay protocol automation results in ease of use by less experienced personnel.

Typical Specifications for the BioHawk LF®	
Characteristic	Description
Exterior air sampling rate	325 liters/min.
Aerosol biodetector- trigger for sampling process	UV bio-fluorescence detector. Average time-to-alarm is 15 seconds.
Air sampling rate for biological aerosol detector	1.2 liters/min.
Bioaerosol detection limit	<100 ACPLA, 90% confidence limit under controlled lab conditions.
Biological sample preparation after trigger signal	Liquid sample: distilled water from wetted-wall cyclone diluted with immunoassay buffer.
Bioassay method	Automated lateral flow immunoassay. Minimum and maximum times-to-detect are 5 and 15 minutes, respectively.
Number of simultaneously identifiable biological agents	Assay ticket specific. One to eight typical.
Bioassay consumables life	Lateral flow immunoassay coupons are provided in an assay-ready hermetic case. Five or more month life in as-supplied state. Single-use product.
Consumables	1) Bulk distilled water and 2) buffer concentrate.
Human interface	Day/night touchscreen LCD display. Usable in MOPP gear.
Process control details	Industrial PC-based control/protocol software. Touch screen control. Fully automated and integrated sampling, sample preparation, bioassay and cleaning protocols. Immediate operator alert upon any detected fault.
Output upon positive result	Immediate light and sound alarms, signal provided for remote alarm.
Ethernet or WiFi connectivity	Yes.
Operating temperature range	4° to 40° C.
Environmental standards, shock and vibration	Appropriate sections of MIL-STD-810.
Power	Universal lump-in-cord power supply, 82-265 V (47-63 Hz).
Physical footprint (cm)	33.8cm H x 19.7cm D x 43.5cm W
Weight	Dry weight: 13 kg
Exterior noise level	70 dB(A)
<i>Research International, Inc. reserves the right to change product and system specifications without prior notice.</i>	

## Research International, Inc.

### U.S. Headquarters Office

17161 Beaton Road SE, Monroe, WA 98272-1034

Phone: 360-805-4930 • Fax: 360-863-0439

Toll Free: 1-800-927-7831

Email: [info@resrchintl.com](mailto:info@resrchintl.com) • Web: [www.resrchintl.com](http://www.resrchintl.com)

### U.S. East Coast Office

Jon Tobelmann

Phone: 703-625-8381

Email: [jontobelmann@resrchintl.com](mailto:jontobelmann@resrchintl.com)

To locate an international distributor, please contact our headquarters office.

